

## Yealink W60B DECT IP Base Station



Product Name: Yealink W60B DECT IP Base Station

Manufacturer: Yealink

Model Number: W60B

### Yealink W60B DECT IP Base Station

The Yealink W60B is the DECT IP base station for small and medium-sized businesses. Paring with up to a total of 8 Yealink W56H DECT handsets, the W60B allows you enjoy mobility and flexibility. A powerful chip ensures a better and higher performance, allowing this DECT IP base station to support up to 8 VoIP accounts and 8 concurrent calls.

### Yealink W60B Key Features

- Up to 8 concurrent calls
- Up to 8 DECT cordless handsets
- Up to 8 VoIP accounts
- Support Opus audio codec
- TLS and SRTP security encryption
- Noise Reduction System

Designed with a modern and elegant style, this compact DECT IP base station possesses a wire-hidden design, with the option to be wall-mounted. By supporting Opus codec, Yealink W60B consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions.

### Yealink W60B - Technical Specifications

#### Phone Features

- Up to 8 concurrent calls
- Up to 8 handsets
- Up to 8 VoIP accounts
- Up to 5 repeaters per base station
- Paging, intercom, auto answer
- Call hold, call transfer, call waiting
- Three-way conference
- Switching between calls
- Mute, silence, DND
- Caller ID with name and number
- Redial
- Anonymous call
- Anonymous call rejection
- Call forward (always/busy/no answer)
- Speed dial
- Voicemail
- Message Waiting Indication (MWI)
- Local phonebook for up to 500 entries (store in the base)
- Remote phonebook/LDAP
- Phonebook search/import/export
- Call history (all/missed/placed/received)
- Direct IP call without SIP proxy
- Reset to factory, reboot
- Emergency call
- Dial plan
- Music on hold
- Broadsoft directory
- BroadSoft call log
- Broadworks feature key synchronisation

## Yealink W60B DECT IP Base Station

• Shared Call Appearance (SCA)

### Management

• Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS  
• Auto-provision with PnP  
• Handset upgrade: OTA (Over-The-Air)/USB port  
• Configuration: browser/phone/auto-provision  
• Trace package and system log export

### Audio Features

• Wideband codec: Opus, AMR-WB (optional), G.722  
• Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC  
• VAD, CNG, AEC, AGC, PLC, AJB  
• Support VQ-RTCPXR (RFC6035)

### Network Features

• SIP v1 (RFC2543), v2 (RFC3261)  
• SNTP/NTP  
• VLAN (802.1Q and 802.1P)  
• 802.1x, LLDP, PPPoE  
• STUN Client (NAT Traversal)  
• UDP/TCP/TLS  
• IP assignment: static/DHCP  
• Support outbound proxy server backup

### Security

• Open VPN  
• Transport Layer Security (TLS)  
• HTTPS (server/client)  
• SRTP (RFC3711)  
• Digest authentication using MD5  
• Secure configuration file via AES encryption  
• Support SHA256/SHA512/SHA384  
• Three-level configuration mode: Admin/Var/User

### DECT

• Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)  
• DECT Standards: CAT-iq2.0

### Interface

• 1 x RJ45 10/100M Ethernet port  
• Power over Ethernet (IEEE 802.3af), Class 1

### Physical Features

• Indoor Range: 20m~50m (The ideal distance is 50m)  
• Outdoor Range: 300m (in ideal conditions)  
• Desktop or wall mountable  
• Energy-saving ECO mode/ECO Mode+

## Yealink W60B DECT IP Base Station

• Three LED indicators on W60B: 1 x Registration LED 1 x Network Status LED 1 x Power Indicator LED

• External Yealink AC adapter; AC 100-240V Input and DC 5V/600mA Output

• Dimension (W\*D\*H): 130mm x 100mm x 25.1mm

• Operating humidity: 10~95%

• Operating temperature: -10~+50°C (+14~122°F)

### Package Features

• Package content: -W60B Base Station-Base Stand-Power Adapter-Ethernet Cable-Quick Start Guide

• Qty/CNT: 10 PCS

• Giftbox size: 205mm\*196mm\*95mm

• Carton measures: 512mm\*414mm\*213mm

• N.W: 3.6 kg

• G.W: 4.3 kg

**Price: £41.40**

Options available for Yealink W60B DECT IP Base Station :

### **DECT Repeater Required**

Not Required, [Yealink DECT Repeater RT30 \(RT30-repeater\) \(+£80.45\)](#).